

NILFISK BR755/855

Better ergonomics,
reliability and cleaning



NILFISK

A thoroughly modern machine for efficient cleaning

Welcome to the modern world of cleaning: a world in which efficiency is essential, where ergonomic and environmental considerations are vital, and where the ability to meet the most demanding customer expectations is paramount.

Nilfisk's generation of ride-on scrubber dryers feature all that modern cleaning professionals demand, and more. Better reliability, outstanding traction, a decibel level low enough to make daytime cleaning possible in even the most sensitive areas, and amazing efficiency in both scrubbing and drying performance.

Added to which there are innovations such as the ecoflex™ concept, for easily adjust of amount of water, precise detergent metering and pressure to the surface. The BR 755/755C/855 series is simply the better choice.



An integrated on-board charger enables easy plug-in and battery charge at any outlet

Built-in squeegee hanging system on recovery tank for easy machine transfer in narrow areas

A debris tray captures the dirt from the suction hose to prevent it from entering the recovery tank

Easy change of cartridge, now located underneath the seat

Both the cleaning deck and the squeegee sides are well protected by large roller bumpers tank



Top features and benefits include:

- Flexible software menu gives a tailored machine to suit the specific application
- Waterproof one touch control panel simplifies operations for better results
- High manoeuvrability allows cleaning in congested areas
- Adjustable scrubbing pressure ensures better results regardless of the dirt level
- Integrated 3 stage vacuum reduces noise levels to just 63 dB(A)
- Unique squeegee design for excellent drying performance
- Large battery compartment enables a 360Ah battery tray for more than 4.5 hours running time
- Robust design ideal for commercial and industrial cleaning such as supermarkets, shopping malls, schools, airports, hospitals, warehouses, food and iron&metal industry



Technical specifications

Description	Unit	BR755	BR755C	BR855
Voltage	V	24	24	24
Rated power	W	2544	2256	2544
Sound pressure level at 1.5 m	dB(A)	63.7	63.7	63.7
Productivity rate theoretical/ actual	m ² /h	4500/3150	4500/3150	5400/3800
Scrubbing width	mm	710	710	860
Max speed	km/h	6.3	6.3	6.3
Solution/recovery tank	l	106/106	106/106	106/106
Brush/pad diameter	mm	2x355	cyl.	2x430
Brush pressure	kg	40/65/96	27/36/45	40/65/96
Brush speed	rpm	250	900	250
Battery compartment size (lxwxh)	mm	667x406x533	667x406x533	667x406x533
Length x width x height (w/o squeegee)	cm	152x77x131	152x80x131	152x92x131
Weight	kg	244	248	246
Operating weight	kg	658	662	660

Nilfisk A/S

Marmorvej 8 · 2100 Copenhagen Ø · Denmark

Tel. +45 43 23 81 00 · mail.com@nilfisk.com

www.nilfisk.com

NILFISK